

Product name	:	BENMAN CLEAR VARNISH		
Reference number	:	High gloss	Matte	Semi-gloss
		28 530	28 531	33 483

Product description

High quality clear varnish to treat surfaces, treated and untreated, of wood, metal, aluminium, glass, stone, and various types of plastic.

Product characteristics

Fast drying
Excellent filling property
Lasting gloss
Scratch free and shock proof
Resistant to weather influences
Corrosion preventive
UV-resistant and non-fading
Excellent adhesion

Physical and Chemical Characteristics

Contents	: 400 ml
Base	: Acrylic resin
Colour	: Transparent
Gloss	: High gloss, Semi-gloss, Matte
VOC-content	: Approximately 90% w/w
Solid content	: Approximately 10% w/w
Coverage	: 1,5 to 1,75 m ²
Dust dry	: After 5 to 10 minutes
Tack free	: After 10 to 20 minutes
Hardened/re-sprayable	: After 2 hours
Heat resistant	: up to 110°C



Usage

Before use, carefully read the directions on the packaging and act accordingly.

Pre Treatment

The surface should be clean, dry and free of grease. Slightly sand the surface (grain 600).

Treatment

The surface should be clean, dry and free of grease. The can should have room temperature. Best application temperature 15 to 25°C. Before use, shake the can for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.

Apply the product in several thin layers. Before applying the next layer, again shake the can.

After use, clean the valve (turn can upside down and press the nozzle for approximately 5 seconds).

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.