

Product name	:	BENMAN CHROME EFFECT		
Colour	:	Silver	Gold	Copper
Reference number	:	28 537	28 536	28 538

Product description

High quality, fast-drying, decorative lacquer to treat surfaces, treated and untreated, of wood, metal, aluminium, glass, stone and various types of plastic.

Product Characteristics

Excellent coverage
Metallic gloss
Not rub resistant
Not resistant to weather influences
Excellent adhesion

Physical and Chemical Characteristics

Contents	:	400 ml
Base	:	Acrylic resin
Colour	:	Chrome Silver Chrome Gold Chrome Copper
VOC-content	:	Approximately 90% w/w
Solid content	:	Approximately 10% w/w
Gloss	:	Metallic
Coverage	:	1,25 to 1,75 m ²
Dust dry	:	After 5 to 10 minutes
Hardened	:	After 24 hours
Heat resistant	:	up to 110°C



Usage

Before use, carefully read the directions on the packaging and act accordingly.

Pre Treatment

The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface. Apply a layer of primer suitable for the surface. After drying, sand the base layer (grain 600).

Treatment

The surface should be clean, dry and free of grease. The can should have room temperature. Best application temperature 15 to 25°C. Before use, shake the can for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeters.

Apply the product in several thin layers. Before applying the next layer, again shake the can.

Not re-sprayable with clear varnish.

After use, clean the valve (turn can upside down and press the nozzle for approximately 5 seconds).

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.