

---

<b>Product name</b>	:	<b>Chain Grease</b>
<b>Article number</b>	:	<b>28 581</b>
<b>Exclusive Distributor</b>	:	<b>Fournarakis S.A.</b>
		<b>9.5 klm Attiki Odos exit 4 Aspropyrgos Athens Greece</b>
		<b>Telephone number + 30 210 55 98 400</b>
		<b>Telefax number + 30 210 55 98 440</b>
		<b>Made in Holland</b>

---

## Product description

High quality spray to lubricate chain-driven transmissions, which are liable to heavy load.

## Applications

Chains  
Chain driven transmissions, liable to heavy load  
Conveyors

## Product characteristics

To be processed like oil, with the properties of grease  
Outstanding mechanical and thermal stability  
Good adhesion  
Dilatant  
Prevents wear and sticking  
Resistant to weather influences  
Resistant to weak acids and bases  
Water-repellent  
Directed jetspray

## Physical and Chemical Characteristics

Contents	:	400 ml
Basis	:	Mineral Oil
VOC-content	:	Approximately 39% w/w
Colour	:	Transparent
Scent	:	Characteristic
Relative density at 20°C	:	0,844 g/ml
Yield	:	2,0 g /sec
Vapour pressure at 20°C	:	3 to 4 bar
4 Ball EP-test (ASTM D 2596)	:	3430 N
Temperature resistant	:	-50°C to + 200°C
pH	:	Neutral



## Usage

**Before use, carefully read the directions on the packaging and act accordingly.**

The aerosol should have room temperature.  
Best processing temperature 5 to 30°C  
Best use, shake the aerosol.

Apply industrial chain grease in a thin layer.  
During the initial flow phase, when the spray can really penetrate the treated chain, the spray has a foaming effect.

Optimum lubrication is obtained after evaporation of the solvent.