
Product name	:	Electro Protect
Article number	:	28 608
Exclusive Distributor	:	Fournarakis S.A.
		9.5 klm Attiki Odos exit 4 Aspropyrgos Athens Greece
		Telephone number + 30 210 55 98 400
		Telefax number + 30 210 55 98 440
		Made in Holland

Product description

High quality electro preservative to prevent starting problems caused by moisture.

Applications

Switches	Spark Plugs
Batteries	Printed Circuit Board Switches
Multiple sockets	Distributor caps
Cables	Fuses
Electric tools	Current distributors
Plugs	
Electrical systems, which should be protected for moisture	



Product characteristics

Water-repellent
Moisture repellent
Good penetrating properties
Excellent adhesion
Excellent corrosion prevention
Resistant to water, salt and weak acids and bases

Physical and Chemical Characteristics

Contents	: 400 ml
Basis	: Mineral Oil
VOC-content	: Approximately 85% w/w
Colour	: Transparent
Scent	: Characteristic
Relative density at 20°C	: 0,802 g/ml
Vapour pressure at 20°C	: 3 to 4 bar
Yield	: 1,9 g/sec
Refractive Index at 20°C	: 1,444
pH-value	: Neutral

Usage

Before use, carefully read the directions on the packaging and act accordingly.

The aerosol should have room temperature.
Best processing temperature 5 to 30°C.

Before use, shake the aerosol.
Switch off electrical installations before treatment.

The parts to be treated must be clean, dry and free of grease.
Apply electro protect in several thin layers.h