

Product name : BENMAN WHITE RADIATOR LACQUER
Reference number : 28 616

Product description

High quality lacquer to embellish and repair radiators and central heating pipes.

Product characteristics

Resistant to heat
Excellent coverage and filling property
Lasting colour and lasting gloss
Scratch free and shock proof
Resistant to cleaners
Corrosion preventive
Good adhesion

Physical and Chemical Characteristics

Contents : 400 ml
Base : Alkyd resin
Colour : White RAL9010
VOC-content : Approximately 82% w/w
Solid content : Approximately 18% w/w
Coverage : 1,25 to 1,75 m²
Dust free : After 30 to 60 minutes
Tack free : After 3 to 4 hours
Hardened/re-sprayable : After 24 hours
Heat resistant : up to 110°C



Usage

Before use, carefully read the directions on the packaging and act accordingly.

Pre Treatment

The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface (grain 600).

Treatment

The surface should be clean, dry and free of grease. The can should have room temperature. Best application temperature 15 to 25°C. Before use, shake the can for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.

Apply the lacquer in several thin layers. Before applying the next layer, again shake the can.

Even when the lacquer has hardened, do not treat with acrylic lacquer or nitro-cellulose lacquer.

After use, clean the valve (turn can upside down and press the nozzle for approximately 5 seconds).

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.