

Product name	: White Lacquer
Article number	: 28 613
Exclusive Distributor	: FF GROUP TOOL INDUSTRIES 9.5 klm Attiki Odos (exit 4) 19300, Aspropyrgos, Athens, Greece Telephone number: + 30 210 55 98 400 Made in the Netherlands

Product description

High quality lacquer to repair small damage to kitchen equipment.

Product characteristics

Excellent coverage and filling property
Lasting colour and lasting gloss
Scratch free and shock proof
Resistant to chemicals
Corrosion preventive
Good adhesion

Physical and Chemical Characteristics

Contents	: 400ml
Base	: Nitro-cellulose binder
Colour	: White
VOC-content	: Approximately 88% w/w
Solid content	: Approximately 12% w/w
Coverage	: 1,25 to 1,75 m ²
Dust dry	: After 5 to 10 minutes
Tack free	: After 10 to 20 minutes
Hardened/re-sprayable	: After 2 hours
Heat resistant	: To 110°C



Usage

Before use, carefully read the directions on the packaging and act accordingly.

Pre Treatment

The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface. Apply a layer of primer suitable for the surface. After drying, sand the base layer (grain 600).

Treatment

The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 15 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.

Apply the lacquer in several thin layers. Before applying the next layer, again shake the aerosol.

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.